

འབྲུག་ ཙན་དན་ཤིང་གི་དྲི་སྒྱུ་མ་གནས་ཚད།

BHUTAN STANDARD

Essential Oil of Bhutan Cypress



ICS 71.100.60

© Copyright 2025

BHUTAN STANDARDS BUREAU

The National Standards Body of Bhutan

THIMPHU 11001

....., 2025

Price group B

འབྲུག་ ཙན་དན་ཤིང་གི་འྲི་སྒྱུ་མ་གནས་ཚད།

BHUTAN STANDARD

Essential Oil of Bhutan Cypress

FDBTS

PDF disclaimer

This PDF may contain embedded typefaces. In accordance with Adobe's Licensing policy, this file may be printed or viewed but shall not be edited unless the typefaces which are embedded are licensed to and installed on the computer performing editing. In downloading this file, parties accept therein the responsibility of not infringing Adobe's licensing policy. The Bhutan Standards Bureau accepts no liability in this area.

Adobe is a trademark of Adobe Systems Incorporated.

COPYRIGHT PROTECTED DOCUMENT

© BSB 2025

All rights reserved. Unless otherwise specified, no part of this publication may be reproduced or utilized in any form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from BSB at the address below in the country of the requester.

Director
Bhutan Standards Bureau
Rijug Lam
Thimphu-11001
Tel: 00975-2-325104/325401
Fax: 00975-2-323712/328298
Web: www.bsb.gov.bt
Published in Thimphu, Bhutan

Contents

FOREWORD	iv
INTRODUCTION	1
1 Scope	2
2 Normative References	2
3 Terms and Definition	2
4 Acronyms and Symbols	3
5 Requirements	4
6 Sampling	5
7 Packaging	5
8 Labelling or Marking	6
9 Storage	6
Annex A	7
Annex B	9
Annex C	11
Annex D	13
Annex E	15
Annex F	18
Annex G	21
Annex H	25
Annex I	26
Bibliography	29

EDBTS

FOREWORD

This Bhutan Standard for the essential oil of Bhutan Cypress was developed by Bhutan Standards Bureau after the draft was finalised by the Pharmaceuticals and Traditional Medicines Technical Committee (TC 05) and approved by the Bhutan Standards Bureau Governing Body on.....

This standard is subject to systematic review after five years to keep pace with the market trends, industrial and technological developments. Any suggestions and further information may be directed to the concerned Technical Committee.

FD B T S

INTRODUCTION

Essential oil of Bhutan Cypress is derived from *Cupressus torulosa* (D. Don), also known as Himalayan Cypress. This species belongs to the Cupressaceae family, a group of coniferous evergreen trees native to temperate and subtropical regions of Asia, Europe, and North America. Bhutan Cypress stands out with its dark green foliage, small yellow flowers, and rounded cones. These trees develop a pyramidal shape during their early growth stages and can reach impressive heights of 25 to 45 meters.

Notable species within this family include the Mediterranean Cypress (*Cupressus sempervirens* L.), Blue Cypress (*Callitris intratropica*), and Bhutan Cypress (*Cupressus torulosa*). Bhutan Cypress, the National Tree of Bhutan, thrives at elevations of 1,800 to 3,000 meters in the Himalayan region, favouring calcareous soils and abundant sunlight. Locally known as “Tsenden,” it holds profound cultural and spiritual significance. It is frequently planted near sacred sites such as monasteries and dzongs. Traditionally, its wood and branches are utilized in the preparation of Sowa Rigpa based medicine, while its aromatic leaves are burned as incense during religious and ceremonial practices.

The tree's thick brown or grey-brown bark peels off in long strips, while its slender branches end in whip-like tips. Cones appear in early spring, maturing by summer, and contribute to the tree's reproduction through their seeds. The essential oil is extracted primarily through steam distillation of the leaves and twigs.

Bhutan Cypress essential oil is celebrated for its medicinal and therapeutic properties, primarily focused on aromatherapy and topical applications. It's known for its refreshing and cleansing effects, aiding in stress reduction and promoting focus. It also helps soothe coughs and colds. Bhutan Cypress essential oil has antibacterial, antimicrobial, and antifungal properties making it useful for skin conditions like acne. However, improper usage can lead to skin irritation, allergic reactions, or toxicity from concentrated compounds, underscoring the importance of correct application and dosage.

Growing demand for Bhutan Cypress essential oil has highlighted the need for stringent measures to prevent adulteration and ensure quality. Substandard products and unsafe practices pose health risks, making robust quality control essential. Establishing national standards is key to safeguarding consumer safety, maintaining product reliability, and promoting sustainable trade.

This standard outlines essential requirements to assess and evaluate the quality and safety of Bhutan Cypress essential oil production. While it establishes minimum quality criteria, certain parameters could not be verified due to limitations in national testing capacity. However, the standard has been developed through consultation with stakeholders to meet its intended purposes to guide manufacturers, regulators, and traders. The primary goals include improving product consistency, facilitating certification and trade, and maintaining product reliability and integrity. Compliance with this standard remains at the discretion of individuals and businesses, and the standard organization or technical committee bears no liability for any adverse health effects or material losses.

འབྲུག་ ཅན་དན་ཤིང་གི་ཁྱུ་མ་གནས་ཚད།

BHUTAN STANDARD

Essential Oil of Bhutan Cypress

1 Scope

This standard specifies essential characteristics of the essential oil of Bhutan Cypress (*Cupressus torulosa* D. Don) from Bhutan to facilitate the assessment of its quality.

2 Normative References

There are no normative references for these documents.

3 Terms and Definition

For the purpose of this standard the following definitions shall apply:

3.1 Adulteration

Adulteration is an act of intentionally debasing the originality of a product either by the admixture or substitution with inferior substances or by the removal of some valuable ingredients.

3.2 Batch

Identified quantity of essential oil, assumed to have uniform characteristics, made up of one or more containers.

3.3 Container

Recipient constituting the whole or part of the batch and containing the essential oil to be sampled.

3.4 Delivery

Quantity of essential oil dispatched at a single time and forming the subject of a specific contract or dispatch document.

3.5 Increment

Quantity of essential oil sampled at a single time at a point in the container to be sampled.

3.6 Optical rotation

Angle, expressed in milliradians and/or degrees of angle, described by the polarization plane of luminous radiation whose wavelength is $589.3 \text{ nm} \pm 0.3 \text{ nm}$, corresponding to the D lines of sodium, when such light travels through a thickness of 100 mm of essential oil under given conditions of temperature.

When the determination is carried out on different thicknesses, the optical rotation value should be computed by reference to a thickness of 100 mm. Additionally, the measurements according to the Faraday magneto-optical principle are possible. The thickness of the sample is approximately 10 mm in that case.

Optical rotation of a solution of essential oil divided by the mass of essential oil in the unit of volume.

3.7 Essential Oil of Bhutan Cypress

Essential oil obtained by steam distillation of the leaves and twigs of Bhutan Cypress (*Cupressus torulosa* D. Don) of the Cupressaceae family growing wild in Bhutan.

3.8 Refractive index

Ratio of the sine of the angle of incidence to the sine of the angle of refraction, when a ray of light of defined wavelength passes from air into the essential oil kept at a constant temperature.

3.9 Relative density at 20°C

Ratio of the mass of a given volume of the oil at 20°C to the mass of an equal volume of distilled water at 20°C.

3.10 Sample

Quantity of essential oil obtained by mixing the different increments of a container. On the basis of the samples, the laboratory may conduct its own sampling plan in view of the analysis.

4 Acronyms and Symbols

cm	: centimetre
g	: grams
GC	: Gas Chromatography
g/l	: gram per litre
M	: mass
Mg	: milligram
ml	: millilitre
mm	: millimetre
mrاد	: milliradians
MS	: mass spectra
m/v	: mass by volume
mol/l	: moles per litre
nm	: nanometre
NMT	: not more than
v/v	: volume by volume
v/w	: volume by weight
w/w	: weight by weight
<	: less than
>	: greater than

5 Requirements

5.1 Description

Essential oil of Bhutan Cypress is a clear transparent pale yellow to light amber liquid with characteristic sweet aroma extracted from the leaves and twigs of the *Cupressus torulosa* (D. Don) using a steam distillation process.

The main chemical constituents of Bhutan Cypress oil include α -pinene, δ -3-carene, limonene, myrcene, and terpinen-4-ol.

5.2 Scientific classification

Kingdom : Plantae
 Phylum : Tracheophyta
 Class : Pinopsida
 Order : Pinales
 Family : Cupressaceae
 Genus : Cupressus
 Species : *Cupressus torulosa* (D. Don)

5.3 Appearance

Clear transparent mobile liquid.

5.4 Colour

Pale yellow to light amber liquid.

5.5 Odour

Characteristic, terpenic, fresh, sweet aroma.

5.6 Tests

5.6.1 Identification test by Gas Chromatography

Analysis of the essential oil of Bhutan Cypress shall be carried out by gas chromatography described in Annex A. In the chromatogram obtained, the representative and characteristic components shown in Table 1 shall be identified. This constitutes the chromatographic profile of the essential oil.

Table 1 — Chromatographic profile of the essential oil of Bhutan Cypress
(Clause 5.6.1)

Component	Minimum %	Maximum %
α -pinene	30	50
β -pinene	0.89	1.2
α -Thujene	1.26	1.5
Sabinene	4.6	19.23
Terpinen-4-ol	2.7	3.8

Limonene	8.5	23.9
δ-3-Carene	6.5	18.7
NOTE: The chromatographic profile is normative		

5.6.2 Relative density

The relative density of essential oil of Bhutan Cypress shall be a minimum of 0.860 and a maximum of 0.910 when determined at 20°C as per the method described in Annex C.

5.6.3 Refractive index

The refractive index of essential oil of Bhutan Cypress shall be minimum of 1.470 and a maximum of 1.490 when determined at 20°C as per the method described in Annex D.

5.6.4 Optical rotation

The optical rotation of essential oil of Bhutan Cypress shall be between +10° to +30° when determined at 20°C as per the method described in Annex E.

5.6.5 Peroxide value

The peroxide value of essential oil of Bhutan Cypress shall be between 0 mmol/l to 20 mmol/l when determined as per the method described in Annex F.

5.6.6 Solubility

One volume of essential oil of Bhutan Cypress mixed with eight volumes of ethanol (90% by volume fraction) shall give a clear solution when determined at 20°C; or

One volume of essential oil of Bhutan Cypress mixed with two volumes of ethanol (95% by volume fraction) shall give a clear solution when determined at 20°C as per the method described in Annex G.

A slight opalescence is sometimes observed.

5.6.7 Flashpoint

The mean value shall be +48°C obtained with Pensky Martens equipment. The information on flashpoints is provided in Annex H.

6 Sampling

Minimum volume of the test sample that allows each of the tests specified in this standard to be carried out at least once is 25 ml. However, the laboratory may conduct its own sampling plan in view of the analysis.

The general rules for a sampling of essential oil of Bhutan Cypress, in order to provide a laboratory with quantities that are suitable to be handled for expertise purposes is described in Annex I.

7 Packaging

The container for storage, in contact with the essential oil, shall not adulterate the composition or affect the activity of the oil. For pharmaceutical grade essential oils, it shall comply with pharmacopoeial requirements and/or ISO/TR 210.

Essential oil of Bhutan Cypress should be packaged in an airtight container preferably glass, tin-lined, or aluminium, which by nature do not change the product and protect it from external attacks.

The essential oil shall be protected from light and stored in a cool and dry place.

In general, the materials of the container shall be inert toward the packed essential oil to avoid overtime damage to the packing material and the essential oil.

8 Labelling or Marking

The labelling materials shall be durable and affixed directly to the container to withstand the transport conditions and avoid tampering and subsequent use for other purposes.

The labelling shall include the following information, however not limited to:

- a) the name of the product/material;
- b) net weight or volume;
- c) batch number;
- d) manufacturing date;
- e) expiry date;
- f) full address of the manufacturing site;
- g) storage conditions; and
- h) disclaimer or caution, if any such as a highly flammable symbol, irritant in nature, etc.

9 Storage

It shall be checked for any liquid or vapour leaks and stored in a cool and dry place, away from direct light and heat.

Annex A
(Normative)
Gas Chromatographic analysis of Essential oil of Bhutan Cypress

A.1 General

The gas chromatography (GC) method describes the general guidelines for the determination of the chromatographic profile of essential oil, as it is one of the specifications that enable assessment of the quality of essential oil. The GC evaluates relative proportions of essential oil content and does not determine the actual concentration of the components. The chromatographic conditions given here are for guidance only.

NOTE The principles of GC and the application of the technique are also described in international pharmacopoeias. For further guidance on chromatographic profiles, refer to ISO 11024-1 Part 1: Preparation of chromatographic profiles for presentation in standards and ISO 11024-2 Part 2: Utilization of chromatographic profiles of samples of essential oils.

A.2 Sample preparation and method

Dissolve a sample of the material in a suitable solvent, such as cyclohexane or petroleum ether. Inject the sample solution into the gas chromatograph, where the carrier gas carries it from one end of the column to the other. The constituents of the sample undergo distribution at different rates and ultimately separate from one another during its movement. As the separated constituents emerge from the end of the column one after another, the signals are detected by suitable means whose response is related to the amount of a specific component leaving the column.

A.3 Apparatus

Use any GC that is capable of being operated under conditions suitable for resolving the individual constituents into distinct peaks. The GC may be operated under the following chromatographic conditions:

Sample	Essential oil of Bhutan Cypress
Column	Fused silica open tubular column
Material	Stainless steel
Length	30 m
Orifice	0.32 mm
Stationary phase	The column is coated with a phase 100% dimethylpolysiloxane.
Carrier Gas	Helium at a constant flow of 3 ml/min.
Conditions	Oven temperature programmed from 60°C - 210°C at 8°C /min and injector at 250°C.
Detector	
Type	Flame ionization
Temperature	250°C

A.4 Calculation

A.4.1 Area Measurements

The area of the peak is measured by multiplying the peak height times the width of the half-height since normal peaks approximate a triangle. The normal peak base is not taken since large deviations may be observed due to tailing or adsorption. When peaks are symmetrical and of reasonable width, this technique is fairly accurate and simple to use.

Other methods, such as triangulation, disc integrators, and electronic digital integrators, can be used for area measurements.

A.4.2 Area Normalisation

For area normalization, the following formula can be used to calculate the percentage composition by measuring the area of each and dividing the individual areas by the total area:

$$\text{Percentage of } A = \frac{\text{Area of } A}{\text{Total Area}} \times 100$$

Relative or indirect calibration method of internal standardization may be used if a pure appropriate internal standard is available

Annex B
(Normative)
Preparation of Test samples

B.1 General

This annexure gives general guidance for the preparation of samples of essential oils to be submitted to a laboratory for analysis. It is applicable, in particular, to those essential oils that cannot be analysed directly; that is those which are solid or partially solid at room temperature or those which are cloudy due to the presence of water or suspended particles.

This method cannot be used for samples for the determination of water.

Filter the essential oil, if necessary, liquefied by heating at a suitable temperature, after the addition of magnesium sulphate or sodium sulphate to eliminate water and the insoluble substances.

B.2 Apparatus

Usual laboratory apparatus and, in particular, the following are required:

- a. Oven
- b. Conical flasks
- c. Suitable filtration equipment

B.3 Reagent

Magnesium sulphate, recently desiccated and neutral or sodium sulphate, recently desiccated.

To desiccate the magnesium sulphate or sodium sulphate, heat to a constant mass at 180°C to 200°C (temperature taken in the continuously stirred material). Grind to a fine powder and keep in a dry flask with an airtight closure.

B.4 Procedure

B.4.1 Essential oils which are solid or partially solid at ambient temperature

Liquefy the essential oil by placing it in the oven maintained at the lowest temperature at which liquefaction may be obtained in less than 10 min. This temperature is usually about 10°C above the presumed freezing point. During this operation, especially in the case of essential oils containing aldehydes, avoid allowing air to enter the container holding the essential oil. To achieve this, loosen, but do not remove, the stopper. Pour the liquefied essential oil into a dry conical flask, previously warmed in the oven to the temperature indicated above, so that the flask is filled to not more than two-thirds of its capacity.

During all subsequent operations, the oil shall be kept at the lowest temperature at which it will remain liquid.

B.4.2 Essential oils which are liquid at the ambient temperature

Transfer the essential oil to a dry conical flask at the same temperature, so that the flask is filled to not more than two-thirds of its capacity.

B.4.3 Treatment of the essential oil

In the two cases indicated above, (B.4.1) or (B.4.2), add to the flask a mass of the dehydrating agent (magnesium sulphate or sodium sulphate) equal to about 15% of the mass of the essential oil. Shake vigorously from time to time over a period of at least 2 hours and filter the sample.

Verify the action of the dehydrating agent by adding about 5% of magnesium sulphate or sodium sulphate and wait for 2 hours before filtering.

The dehydrating agent should still be in a powdery form and the oil should be clear and limpid. In the first case (B.4.1), carry out the filtration in the oven at the appropriate temperature (see B.4.1), but do not keep the essential oil in the oven longer than necessary.

NOTE 1 These operations should immediately precede the analysis. If not, the filtered essential oil should be kept in a cool place protected from strong light, in a previously dried, well-filled container fitted with an airtight closure.

NOTE 2 In certain cases and where required, the metallic phenolates which colour the essential oil should be eliminated by agitation with citric or tartaric acid.

FDBTS

Annex C
(Normative)
Determination of Relative Density at 20°C

C.1 General principle

Equal volumes of the essential oil and water, at 20°C, are weighed successively in a pycnometer.

C.2 Apparatus

Ordinary laboratory apparatus and in particular the following are required:

- a. Glass pycnometer, of minimum nominal capacity of 5 ml.
- b. Water bath, capable of being maintained at $20^{\circ}\text{C} \pm 0.2^{\circ}\text{C}$.
- c. Standardized thermometer, graduated from 10°C to 30°C , with 0.2°C or 0.1°C divisions.
- d. Analytical balance, accurate to 0.001 g.

For routine controls and accurate measurement of the relative density, automatic electronic instruments that are available from the market may be used. However, in case of dispute, the reference method is the pycnometer method.

C.3 Reagents

Distilled water, freshly boiled and subsequently cooled to approximately 20°C.

C.4 Sampling

It is important that the laboratory receive a representative sample which has not been damaged or modified during transportation or storage. A recommended sampling method is given Annex I.

C.5 Procedure

C.5.1 Test sample

Prepare the test samples according to the method in Annex B.

C.5.2 Preparation of pycnometer

Carefully clean the pycnometer and then rinse it successively with, for example, ethanol and acetone, then dry the interior by means of a blower.

If necessary, wipe the outside with a dry cloth or filter paper.

When temperature equilibrium is reached between the balance case and the pycnometer, weigh the latter with its stopper, if any, to the nearest 1 mg.

C.5.3 Weighing of Distilled Water

Fill the pycnometer with distilled water.

Immerse the pycnometer in the water bath. After 30 min, adjust the water to the mark, if necessary. Insert the stopper, if any, and dry the outside as before with a dry cloth or filter paper.

When temperature equilibrium is reached between the balance room and the pycnometer, weigh the latter and its stopper, if any, to the nearest 1 mg.

C.5.4 Weighing of essential oil

Empty the pycnometer, then wash it and dry it as specified in C.5.2.

Proceed as specified in C.5.3, replacing the water with the test sample prepared according to clause C.5.1

C.6 Expression of results

The relative density, d_{20}^{20} , is given by the following equation:

$$\frac{m_2 - m_0}{m_1 - m_0}$$

where,

m_0 is the mass, in grams, of the empty pycnometer determined in C.5.2;

m_1 is the mass, in grams, of the pycnometer filled with distilled water, determined according to C.5.3;

m_2 is the mass in grams, of the pycnometer filled with the essential oil, determined according to C.5.4.

Express the result to three decimal places. In practice, no correction is made for the upthrust due to air.

If the absolute density of the essential oil is required, multiply the value obtained for the relative density by the absolute density of water at 20°C (i.e., 0.99823 g/ml).

C.7 Test report

The test report shall state the method used; the result obtained; and if repeatability has been verified, the final result obtained.

It shall also mention any operating conditions as well as any circumstances that might have influenced the results. The test report shall include all details required for the complete identification of the sample

Annex D
(Normative)
Determination of Refractive Index

D.1 Principle

Depending on the instrument being used, observe the limit of total reflection or take a direct measurement of the angle of refraction while maintaining the oil under isotropism and transparency conditions.

D.2 Apparatus

- a. Refractometer, allowing direct readings of refractive indices between 1.3000 and 1.7000 to be made with an accuracy of ± 0.0002 .
- b. Thermostat or apparatus for temperature maintenance, which ensures a circulation of water through the refractometer, thus keeping the instrument at the reference temperature to within $\pm 0.2^{\circ}\text{C}$.
- c. A light source, sodium light. Diffused daylight or light from an electric lamp may be used for refractometers fitted with an achromatic compensator.
- d. A plate of glass (optional), of known refractive index.

D.3 Reagents

Standard products, of refractometry grade, to adjust the refractometer, as follows.

- a. Distilled water, of refractive index 1.3330 at 20°C .
- b. p-Cymene, of refractive index 1.4906 at 20°C .
- c. Benzyl benzoate, of refractive index 1.5685 at 20°C .
- d. 1-Bromonaphthalene, of refractive index 1.6585 at 20°C .

D.4 Sampling

It is important that the laboratory receive a representative sample which has not been damaged or modified during transportation or storage. A recommended sampling method is given in Annex I.

D.5 Procedure

D.5.1 Preparation of test sample

Prepare the test samples according to the method in Annex B. The temperature of the test sample should be the same temperature at which the measurements shall be made.

D.5.2 Regulation of the refractometer

D.5.2.1 Regulate the refractometer by measuring the refractive index of the standard products described in D.3 (a to d).

D.5.2.2 Verify that the refractometer is maintained at the temperature at which the readings shall be made. This temperature shall not differ from the reference temperature by more than $\pm 0.2^{\circ}\text{C}$ during the test.

The reference temperature is 20°C, except for those oils which are not liquid at this temperature, in which case a temperature of 25°C or 30°C, depending on the melting point of these essential oils, shall be used.

D.6 Determination

Place the test sample, prepared according to D.5.1, in the refractometer. Wait until the temperature is stable and make the measurements.

D.7 Calculation

The refractive index n_D^t , at the specified temperature t , is given by the equation:

$$n_D^t = n_D^{t'} + 0.0004(t' - t)$$

where,

$n_D^{t'}$ is the reading taken at the working temperature t' at which the determination was actually made.

Express the result to four decimal places.

D.8 Repeatability

The absolute difference between two independent single test results, obtained using the same method on an identical essential oil in the same laboratory by the same operator using the same equipment within a short interval of time will, in not more than 5% of cases be greater than ± 0.0002 .

D.9 Test report

The test report shall state the sampling method used; the test method used; the test result obtained; and if repeatability has been checked, the final result obtained.

It shall also mention any operating conditions as well as any circumstances that might have influenced the results. The test report shall include all details required for the complete identification of the sample.

Annex E
(Normative)
Determination of Optical Rotation

E.1 Principle

This is the general method for determining the optical rotation of essential oils such as lemongrass oil. When dealing with solid oils, partially solid oils, oils that are highly viscous at room temperature, or highly coloured oils, this determination is carried out on a solution of the oil.

E.2 Apparatus

- a. Polarimeter, having a precision of at least ± 0.5 mrad ($\pm 0.03^\circ$) and adjusted to give 0° and 180° with water.

The polarimeter shall be checked with a quartz plate of known optical rotation or, if that is unavailable, with an aqueous solution containing 26.00g of anhydrous pure saccharose per 100 ml of solution. The optical rotation of this solution shall be $+604$ mrad ($+34.62^\circ$) in a 200 mm layer, at a temperature of 20°C .

The instrument shall be under conditions of stability when in use, and non-electronic instruments shall be used in the dark.

- b. The light source, comprising any device giving the light of wavelength $589.3\text{ nm} \pm 0.3\text{ nm}$, preferably a sodium vapour lamp.
- c. Polarimeter tubes, usually $100\text{ mm} \pm 0.5\text{ mm}$ long.

When testing slightly coloured samples of low optical rotation, tubes of length $200\text{ mm} \pm 0.5\text{ mm}$ may be used. Tubes of length $50\text{ mm} \pm 0.05\text{ mm}$ or $10\text{ mm} \pm 0.05\text{ mm}$ or even less may be used, if necessary, for strongly coloured samples.

For determination at 20°C or at another specified temperature, use double-walled tubes, equipped with a thermometer to ensure water circulation at the required temperature.

For determination at ambient temperature, any type of tube may be used, although it is advisable to use the type described above in this case too.

- d. Thermometer, graduated in 0.2°C or 0.1°C , allowing determination of temperatures between 10°C and 30°C .
- e. A thermostatically controlled device, for maintaining the temperature of the sample at $20^\circ\text{C} \pm 0.2^\circ\text{C}$ or any other specified temperature.

E.3 Reagents

Reagents shall be of analytical grade. Use distilled water or water of at least equivalent purity.

Solvent (only for essential oils that need to be tested in solution). Use preferably 95% ethanol by volume. It is advisable to check that the optical rotation of the solvent used is nil.

E.4 Sampling

It is important that the laboratory receive a representative sample which has not been damaged or modified during transportation or storage. A recommended sampling method is given in Annex I.

E.5 Procedure

E.5.1 Preparation of test sample

Prepare the test samples according to the method in Annex B.

When determining the specific rotation of essential oil in solution, prepare the oil solution in the appropriate solvent, at the concentration specified for the essential oil being analysed.

E.5.2 Determination

Switch on the light source and wait until full luminosity is obtained.

If necessary, bring the temperature of the test sample to $20^{\circ}\text{C} \pm 1^{\circ}\text{C}$ or to another specified temperature, then pour the sample into the appropriate polarimeter tube, which should be at approximately the same temperature. Start water circulation under thermostatic control so as to keep the whole at the specified temperature ($\pm 0.2^{\circ}\text{C}$) during the determination.

Fill the tube with the test sample, and ensure the absence of air bubbles.

Place the tube in the polarimeter and read the dextrorotatory (+) or laevorotatory (–) optical rotation of the oil on the scale of the instrument.

E.5.3 Number of determinations

Carry out at least three determinations with the same test sample.

Take as the result the mean of the values obtained for three measurements, provided that they do not differ by more than 1.4 mrad (0.08°).

E.6 Expression of results

E.6.1 Calculation and formulae

a. Optical Rotation

The optical rotation, expressed in milliradians and/or degrees of angle, is given by the equation:

$$\alpha_D^t = \frac{A}{l} \times 100$$

where,

A is the value of the angle of rotation in milliradians and/or degrees of angle;

l is the length of the tube used, in millimetres.

Mark as positive (+) dextrorotatory optical rotations and as negative (–) laevorotatory ones.

When polarimeter tubes with double walls for water circulation are not available, it is necessary to apply appropriate correction factors according to the oils tested (for instance, for citrus oils and for some essential oils for which correction factors are known).

These correction factors should be given in the specifications of the oils in question.

b. The optical rotation of oil in solution, the so-called “specific rotation”

The specific rotation, expressed in milliradians and/or degrees of angle, is given by the equation:

$$[\alpha] = \frac{\alpha_D^t}{c}$$

where

α_D^t is the optical rotation of the oil solution, calculated according to E.6.1 a;

c is the concentration of the oil solution, in grams of oil per millilitre of solution.

E.6.2 Precision

The precision of the test method is ± 3 mrad ($\pm 0.17^\circ$).

E.7 Test report

The test report shall state the sampling method used; the test method used; whether an oil in solution was used in the test, specifying the nature of the solvent and the concentration of the oil; the test result obtained; and if repeatability has been checked, the final result obtained.

It shall also mention any operating conditions as well as any circumstances that might have influenced the results. The test report shall include all details required for the complete identification of the sample.

Annex F
(Normative)
Determination of Peroxide Value

F.1 Principle

The peroxide value is the measure of the oxidation present in an essential oil. The method is a redox titration, specifically of the iodometry type. Iodide ions in the essential oil oxidises when they react with peroxides, producing iodine that is then titrated with thiosulfate. This titration can be done using either volumetric or potentiometric methods.

Potentiometric titration is recommended for essential oils that are highly coloured and may have difficulty showing a clear endpoint with coloured indicators, such as vetiver essential oil.

F.2 Reagents

During the analysis, only reagents of recognized analytical grade and reverse osmosis or distilled or deionized water should be used.

- a. Trichloromethane, 99% (volume/fraction) or cyclohexane 99.5% (volume/fraction) for laboratories with restrictions on the use of chloroform.
- b. Glacial acetic acid 99.5% (volume/fraction). Degassed with a fresh pure and dry inert gas (carbon dioxide or nitrogen).
- c. Potassium iodide saturated solution in deionised water, freshly prepared. The solution has to be kept protected from light.
- d. Sodium thiosulfate solution, 0.01 mol/l (0.01 N) or 0.1 mol/l (0.1 N).
- e. Coloured standard indicator, starch solution 1% (volume/fraction). It is not necessary for potentiometric titration.

F.3 Apparatus

Usual laboratory apparatus and, in particular, the following.

- a. Balance ± 1 mg.
- b. Erlenmeyer flask of capacity 250 ml.
- c. Shaker.
- d. Pipettes of capacity 1 ml, 10 ml, graduated in 0.1 ml.
- e. Burette of capacity 10 ml graduated in 0.05 ml.
- f. Test tubes of capacity 50 ml, 100 ml.
- g. Potentiometer.

F.4 Sampling

It is important that the laboratory receive a representative sample which has not been damaged or modified during transportation or storage. A recommended sampling method is given in Annex I.

F.5 Preparation of test sample

Prepare the test samples according to the method in Annex B.

BTS XXX: 2025

The test sample for determining the peroxide value should be taken first, and the peroxide value should be calculated immediately. Homogenize the sample, ideally without heating or aeration. Avoid direct sun exposure. Carefully heat solid samples to 10°C above their melting point. Samples with visible impurities shall be filtered.

Some products may include less than 5 g of extracted essential oil or could contain over 30 meq of active oxygen per kilogram of essential oil. The user should pick a smaller sample mass in these circumstances.

F.6 Procedure

F.6.1 Test portion

10 mm of the essential oil to be titrated should be added to an Erlenmeyer flask.

F.6.2 Determination

20 ml of trichloromethane or cyclohexane, 30 ml of glacial acetic acid, and 1 ml of potassium iodide, saturated solution should be added to a test tube, and if volumetric titration is being done, 2 drops of starch solution should also be added.

Shake for approximately 1 min. The dissolution acquires an orangey colour. Add about 100 ml of distilled water.

Titrate with sodium thiosulfate solution. Use 0.1 mol/l when the expected peroxide values are over 20 mmol/l. Use 0.01 mol/l sodium thiosulfate solution when the expected peroxide value is less than 20 mmol/l. The end point is obtained when the dissolution becomes white.

Perform a blank titration in the same circumstances. Consumption of sodium thiosulfate solution should not exceed 0.5 ml of 0.01 mol/l.

F.6.3 Automated Potentiometric titration

If automated equipment for titration is used, consider the following:

- Use amber beaker glasses to prevent the formation of iodine while the sample is still in the tray if the system uses an autosampler.
- If addition of potassium iodide is automated, prepare 70 % (volume/fraction) solution in distilled water instead of saturated solution, fill an opaque bottle, and replace it every week. The addition of potassium iodide in I.6.2 should be 10 ml instead of 1 ml.

F.7 Expression of results

F.7.1 Calculation

The peroxide value, IP , in mmol/l, is given by Formula:

$$IP = (V_1 - V_0) \times (N_{titrant}) \times 50$$

where,

V_1 is the volume, in millilitres, of titrant sodium thiosulphate, used in the main test;

BTS XXX: 2025

V_0 is the volume, in millilitres, of titrant sodium thiosulphate, used in the blank test;

N_{titrant} is the concentration of titrant, sodium thiosulphate, 0.1 N.

F.7.2 Conversion from mmol/l to meq/kg

The conversion from mmol/l to meq/kg is calculated by Formula:

$$\frac{\text{meq}}{\text{kg}} = \frac{\text{mmol}}{\text{l}} \times \frac{2}{\text{density}} (\text{kg/l})$$

F.8 Precision

F.8.1 Repeatability

The absolute difference between two separate test results obtained from the same essential oil using the same method, by the same operator, in the same laboratory, with the same equipment, and within a short timeframe, did not exceed 5% in absolute values or 0.1 in relative values.

F.8.2 Reproducibility

The absolute difference between two individual tests conducted using the same method on the same essential oil, but in different laboratories with different operators and equipment, did not exceed 10% in absolute values or 0.3 in relative values.

Annex G
(Normative)
Evaluation of Solubility in Ethanol

G.1 Principle

This annex specifies a method for the evaluation of the solubility or miscibility of essential oils with mixtures of ethanol and water of known ethanol content.

An ethanol solution of suitable concentration should be gradually added to an essential oil, at a temperature of 20°C. Evaluate the miscibility and possibly of opalescence.

G.2 Classification of solubility or miscibility

G.2.1 An essential oil is said to be miscible with V volumes or more of ethanol of a given concentration, at a temperature of 20°C, when the mixture of 1 volume of the oil in question with V volumes of that ethanol is clear and remains so after further gradual addition of ethanol of the same concentration up to a total of 20 volumes.

G.2.2 An essential oil is said to be miscible with V volumes of ethanol of a given concentration, at a temperature of 20°C, and to become cloudy when diluted in V' volumes, when the mixture of 1 volume of the oil in question with V volumes of the ethanol is clear and becomes cloudy after further gradual addition of $(V' - V)$ volumes of ethanol of the same concentration and remains cloudy after further addition of the ethanol up to a total of 20 volumes.

G.2.3 An essential oil is said to be miscible with V volumes of ethanol of a given concentration, at a temperature of 20°C, and to become cloudy when diluted in V' to V'' volumes, when the mixture of 1 volume of the oil in question with V volumes of the ethanol is clear, becomes cloudy after further gradual addition of $(V' - V)$ volumes of ethanol of the same concentration, and again becomes clear after further addition of $(V'' - V')$ volumes of ethanol of the same concentration.

G.2.4 An essential oil is said to be miscible with opalescence when the mixture of the oil with ethanol of a given concentration (under the conditions as given in F.2.1, F.2.2 and F.2.3) shows an opalescence identical to the one of the standard solutions for opalescence, freshly prepared in accordance with the method given in F.4 (c).

NOTE The numerical values of V , V' and V'' are not more than 20.

G.3 Apparatus

Ordinary laboratory apparatus and, in particular, the following are required:

- a. Burette, of capacity 25 ml or 50 ml
- b. One-mark pipettes, capable of delivering 1 ml, or analytical balance, capable of weighing to the nearest 1 mg, as appropriate.
- c. Measuring cylinder or flask, of capacity 25 ml or 30 ml, provided with a stopper which is inert to either ethanol or essential oil to be examined.
- d. A device capable of maintaining a temperature of 20°C ± 0.2°C.

- e. Calibrated thermometer, graduated at 0.2°C or 0.1°C, allowing the temperature of the device to be checked.

G.4 Reagents

Use only reagents of recognized analytical quality and distilled water.

- a. Ethanol (95% volume fraction)
- b. Mixtures of ethanol and water.

Mixtures of ethanol and water with an ethanol content of 50%, 55%, 60%, 65%, 70%, 75%, 80%, 85%, 90% and 95% (volume fraction) are normally used.

To prepare these mixtures, add distilled water to ethanol, following the directions given in Table 1, and check their concentrations with an alcoholmeter or a densimeter.

- c. Standard solution for opalescence

Add 0.5 ml of a silver nitrate solution, ($AgNO_3$) = 0.1 mol/l, to 50 ml of sodium chloride solution, (NaCl) = 0.0002 mol/l; then add 1 drop of concentrated nitric acid ($p_{20} = 1.38$ g/ml). Stir the solution and allow it to stand for 5 minutes. Keep away from direct light.

Prepare the solution freshly before use.

G.5 Sampling

It is important that the laboratory receive a representative sample which has not been damaged or modified during transportation or storage. A recommended sampling method is given in Annex I.

G.6 Procedure

G.6.1 Preparation of test sample

Prepare the test samples according to the method in Annex B.

G.6.2 Test Sample

With a pipette, introduce into the measuring cylinder or flask 1 ml of the oil. Place the cylinder and its contents in the device, maintained at a temperature of $20^\circ\text{C} \pm 0.2^\circ\text{C}$.

NOTE When the physical state of the essential oil does not permit the use of a pipette, weigh, to the nearest 1 mg, $1\text{ g} \pm 0.005\text{ g}$ of essential oil. In this case, the definition and the results will be expressed in mass/volume.

G.6.3 Determination of Solubility

Using the burette, add a mixture of ethanol and water of known concentration, which has previously been brought to a temperature of $20^\circ\text{C} \pm 0.2^\circ\text{C}$, in increments of 0.1 ml until complete miscibility occurs, shaking vigorously after each addition. When the mixture is perfectly clear, record the volume of the water/ethanol mixture added.

Continue adding the mixture of ethanol and water in increments of 0.1 ml, up to a total of 20 ml, and shake after each addition. If the mixture becomes cloudy or opalescent before the total addition is completed,

record the volume added at the point where cloudiness or opalescence appears and, if applicable, the volume at which one or the other disappears.

If a clear mixture is not obtained after 20 ml of solvent has been added, repeat with the next higher concentration of the mixture of ethanol and water given in Table 1.

G.6.4 Opalescence

If a clear mixture cannot be obtained but an opalescent mixture is obtained, compare its opalescence with that of the standard solution, as detailed in F.7.2.

G.7 Expression of results

G.7.1 Miscibility

The miscibility of the essential oil with ethanol of concentration Q (see Table 1), at a temperature of 20°C, is expressed as follows:

a) Case F.2.1

1 volume of essential oil in V volumes of ethanol of concentration Q ;

b) Case F.2.2

1 volume of essential oil in V volumes of ethanol of concentration Q with cloudiness from V' volumes of ethanol of the same concentration;

c) Case F.2.3

1 volume of essential oil in V volumes of ethanol of concentration Q with cloudiness appearing between V' and V'' volumes of ethanol of the same concentration;

Where,

V is the volume, in millilitres, of ethanol of concentration Q needed to obtain a clear solution;

V' is the volume, in millilitres, of ethanol of concentration Q needed to produce cloudiness, following the clearness, if it occurs;

V'' is the volume, in millilitres, of ethanol of the same concentration Q at which cloudiness disappears, if it occurs.

Express the values of V , V' and V'' numerically to one decimal place.

G.7.2 Opalescence

If only opalescence occurs (see F.2.4), report whether the opalescence is "greater than", "equal to" or "less than" that of the standard solution (F.4c).

G.8 Test report

The test report shall state the method used; the concentration Q of the ethanol used; and the result obtained.

It shall also mention any operating conditions as well as any circumstances that might have influenced the results. The test report shall include all details required for the complete identification of the sample.

Table 1 — Preparation of the mixtures of ethanol and water

Dilution: ml of ethanol in 100 ml of a mixture, to the nearest 0.1%	Volume of distilled water at 20°C to be added to 100 ml of ethanol (95% volume fraction), at the same temperature \pm 0.1°C, for preparation of the corresponding dilutions.	Mass of ethanol (95% volume fraction)	Mass of water to be added	Values of the relative density and apparent density	
				1)	2)
				d_{20}^{20} ± 0.0001	ρ_{20} ± 0.00001 g/ml
Q % (volume fraction)	ml	G	g		
50	95.76	45.9	54.1	0.9318	0.93014
55	77.90	51.1	48.9	0.9216	0.91996
60	62.92	56.4	43.6	0.9108	0.90911
65	50.15	61.8	38.2	0.8993	0.89765
70	39.12	67.5	32.5	0.8872	0.88556
75	29.47	73.4	26.6	0.8744	0.87279
80	20.94	79.5	20.5	0.8608	0.85927
85	13.31	85.9	14.1	0.8604	0.84485
90	6.40	92.7	7.3	0.8307	0.82818
95	0.0	100.0	0.0	0.8129	0.81138
1) Reference: Swiss Federal Bureau of Weights and Measurements. 2) Reference: International Organization of Legal Metrology.					

**Annex H
(Informative)
Flashpoint**

H.1 General information

The information on flashpoints of the essential oil which are mostly flammable is required for safety purposes by companies such as transport and insurance.

Given that there is a wide variation in the chemical composition of oil, the sample volume needed and the availability of different equipment, it is difficult to recommend a single apparatus for standardization purposes.

The equipment with which the provided flashpoint value was obtained should be specified.

H.2 Flashpoint of the essential oil

The mean value is +48°C.

NOTE Further guidance on flashpoint determination can be found on ISO Technical report ISO/TR 11018:1997 Essential oils – General guidance on the determination of flashpoint.

Annex I (Normative) Sampling

I.1 Principle

The organoleptic, physical and chemical characteristics of batches of essential oils are determined by means of an examination of the samples.

This annex describes the general rules for the sampling of essential oils, in order to provide a laboratory with quantities that are suitable to be handled for expertise purposes.

In the presence of a high content of water or other foreign bodies, this method may only be applicable to the “essential oil” fraction free from water and impurities.

I.2 Apparatus

The sampling devices and the related instruments shall be made of materials which do not affect the sampled essential oil.

The type of apparatus required for sampling should be adapted to the volume to be sampled: e.g. cylindrical probes, pipettes, and bottom sampler.

I.3 Sampling

I.3.1 Inspection

The inspection concerns the physical condition of the delivery, the integrity of the containers, the state of the guarantee systems (lead seals, crown caps, etc.), the designation and the contractual inscriptions.

On opening, conserve the guarantee systems.

I.3.2 Shaking

Prior to any sampling, shake the essential oil using means suited to both the volume and the shape of the recipient.

Those essential oils that are known to crystallize or to thicken should be slowly warmed to a suitable temperature to dissolve crystals or crystalline mass, before shaking. This action shall not alter the composition of the essential oil.

I.3.3 Sampling method

All sampling operations shall be performed immediately after an appropriate shaking.

Take sample three increments per container at a single time, as follows:

- a. take the first increment from the section corresponding to 20% of the container height;
- b. take the second between 40% and 60% of the container height;

- c. take the third at over 90% of the container height.

Gather together the three equal part increments and mix them. After shaking, take 30 ml, which constitutes the sample.

The number of samples per container for the laboratory shall be equal to the number of parts concerned plus a reference sample.

I.4 Packaging and labelling of laboratory samples

I.4.1 Packaging

Use glass or inert material bottles which protect the essential oil against the light.

Pack the samples in clean, dry recipients.

The nature of the recipient shall not alter the essential oil.

Leave a headspace of 2 ml between the essential oil and the stopper to allow for expansion. This space shall not be too great in order to limit possible oxidation due to the air.

Close the recipients using crown tops or new stoppers which do not have any reaction on the product.

Close each sample by means of a guarantee system such that it is inaccessible without breaking the seal.

Ascertain the air tightness.

I.4.2 Marking

The label shall be attached to each of the samples and shall bear indications enabling the traceability of the product, for example;

- a. the sampling date;
- b. the nature of the product: goods and origin;
- c. the name of the supplier;
- d. the batch number;
- e. the serial number of the sample out of the total number of containers.

The information on the label shall be marked in indelible ink.

I.4.3 Conservation

Store the samples intended for the laboratory, protected from light, at a temperature which guarantees their quality.

I.4.4 Dispatch

The packaging shall meet the requirements of the postal services or of the other bodies involved in the transport of the sample within the relevant country (countries).

I.5 Sampling report

The sampling report shall indicate:

- a. the identification of the supplier;
- b. the product identification marks;
- c. the origin;
- d. the batch number;
- e. the quantity represented in grams, kilograms or tons;
- f. the nature and the number of containers;
- g. the presence or absence of the guarantee systems;
- h. the date and time of sampling;
- i. the name, signature and function of the person who carried out the sampling.

The sampling report shall give the physical condition of the sampled essential oil. It shall also indicate the technique employed, if different from that described in this annex, as well as all circumstances which may have influenced the sampling.

A satisfactory sampling operation therefore needs to provide, for analysis, samples representative of the batches from which they originate without modification of the original composition.

FDBTS

Bibliography

- 1] ISO/TR 21092, Essential oils — Characterization
- 2] ISO/TR First edition 1997-03-15 11018, Essentials Oil — General Guidance on determination of flash points
- 3] ISO/TR 211 First edition 1999-03-01, Essentials Oil — General rules for labelling and marketing of containers
- 4] ISO/TR 210 First edition 1999-03-01 Essentials Oil — General rules for packaging, conditioning and storage
- 5] ISO 18321 First edition 2015-05-15, Essential oils — Determination of peroxide value
- 6] ISO 11024-1 First edition 1998-12-01, Essential oils — General guidance on chromatographic profiles — Part 1: Preparation of chromatographic profiles for presentation in standards.
- 7] ISO 11024-2 First edition 1998-12-01, Essential oils — General guidance on chromatographic profiles — Part 2: Utilization of chromatographic profiles of samples of essential oil
- 8] ISO 875 Second edition 1999-09-15, Essential oils — Evaluation of miscibility in ethanol
- 9] ISO 592 Second edition 1998-11-15, Essential oils — Determination of optical rotation
- 10] ISO 356 Second edition 1996-12-15, Essential oils - Preparation of test samples
- 11] ISO 280 Second edition 1998-11-15, Essential oils — Determination of refractive index
- 12] ISO 279 Second edition 1998-12-15, Essential oils — Determination of relative density at 20°C — Reference method
- 13] ISO 212 Second edition 2007-03-15, AMENDMENT 1 2012-08-01 Essential oils — Sampling — AMENDMENT 1
- 14] ISO 212 Second edition 2007-03-15, Essential oils — Sampling
- 15] Lohani H, Gwari G, Andola HC, Bhandari U, Chauhan N. α -Pinene Rich Volatile Constituents of *Cupressus torulosa* D. Don from Uttarakhand Himalaya. *Indian J Pharm Sci.* 2012 May;74(3):278-80. doi: 10.4103/0250-474X.106078. PMID: 23440249; PMCID: PMC3574543.
- 16] Gupta, Sahil & Bhagat, Madhulika & Sudan, Rasleen. (2018). Analysis of chemical composition of *Cupressus torulosa* (D.Don) essential oil and bioautography guided evaluation of its antimicrobial fraction. *Indian journal of experimental biology.* 56.
- 17] Yeshi, K., Aagaard-Hansen, J., Wangchuk, P. (2021). Medicinal, Nutritional, and Spiritual Significance of Plants in Bhutan: Their Biodiscovery Potential and Conservation Status. In: Abbasi, A.M., Bussmann, R.W. (eds) *Ethnobiology of Mountain Communities in Asia*. *Ethnobiology*. Springer, Cham. https://doi.org/10.1007/978-3-030-55494-1_1

**PHARMACEUTICAL AND TRADITIONAL MEDICINES TECHNICAL COMMITTEE
(TC05)**

Organization

Representative(s)

Menjong Sorig Pharmaceuticals Corporation Ltd.,
Thimphu

Mr. Sherab Tenzin
(Chairperson)

Bhutan Food and Drug Authority, MoH

Ms. Sangay Choden

Competition and Consumer Affairs Authority, MoCE

Ms. Tshering Dema

Department of Medical Products, NMS

Mr. Dorji Gyeltshen

National Biodiversity Centre, MoAL

Mr. Leki Wangchuk

Royal Centre for Disease Control, MoH

Mr. Amin Ngawang Tashi

Bhutan Standards Bureau

Mr. Lobzang Dorji
Director
(Ex-officio member)

Member Secretary
Ms. Cheten Zangmo
Standardization Division
Bhutan Standards Bureau